

PRODUCT-DETAILS

TAE75-40-00 36-65V DC

TAE75-40-00 36-65V DC Contactor



General Information

Extended Product Type	TAE75-40-00 36-65V DC
Product ID	1SBL419261R5400
EAN	3471522115737
Catalog Description	TAE75-40-00 36-65V DC Contactor
Long Description	TAE75 4-pole contactors are mainly used for controlling non-inductive or slightly inductive loads (i.e. resistance furnaces...) and generally for controlling power circuits up to 690 V AC and 440 V DC. The contactors can also be used for many other applications such lighting... The TAE... series 4-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 4 N.O. main poles, front and side-mounted add-on auxiliary contact blocks - Control circuit: DC operated with standard double-winding DC coils (with add-on factory-mounted lagging contact for insertion of the "holding" winding). TAE... contactors offer a large coil voltage range - Accessories: a wide range of accessories is available.

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	142 mm
Package Level 1 Depth / Length	190 mm
Package Level 1 Height	136 mm
Package Level 1 Gross Weight	1.43 kg
Package Level 1 EAN	3471522115737
Package Level 2 Units	box 8 piece
Package Level 2 Gross Weight	11.44 kg

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SBD250804U1000
Environmental Information	1SBD250025E1003
GOST Certificate	GOST_POCCFRME77B07175
Instructions and Manuals	FPTC407701P0003
RoHS Information	1SBD250804U1000
UL Certificate	UL_20120830-E312527-10-1
UL Listing Card	UL_E312527

Environmental

Ambient Air Temperature	Close to Contactor for Storage -60 ... +80 °C Near Contactor for Operation in Free Air -40 ... +55 °C
Climatic Withstand	acc. to IEC 60068-2-30 and 60068-2-11 - UTE C 63-100 specification II
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 20 K40 Shock Direction: B2 15 K40 Shock Direction: C1 20 K40 Shock Direction: C2 20 K40 Closed, Shock Direction: B1 10 K40 Open, Shock Direction: B1 5 K40
RoHS Status	Following EU Directive 2011/65/EU

Technical

Number of Main Contacts NO	4
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 125 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 125 A (690 V) 55 °C 105 A
Rated Operational Current AC-3 (I_e)	(1000 V) 55 °C 28 A (220 / 230 / 240 V) 55 °C 75 A (380 / 400 V) 55 °C 75 A (415 V) 55 °C 72 A (440 V) 55 °C 70 A (500 V) 55 °C 65 A

	(690 V) 55 °C 46 A
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I _e AC-3
Short-Circuit Protective Devices	gG Type Fuses 160 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 1300 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 630 A
Maximum Electrical Switching Frequency	AC-1 300 cycles per hour AC-2 / AC-4 150 cycles per hour AC-3 300 cycles per hour
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	DC Operation 36 ... 65 V
Coil Consumption	Pull-in at Max. Rated Control Circuit Voltage DC 450 W Holding DC (U _{min} / U _{max}) 1.7 / 6.5 W Pull-in DC (U _{min} / U _{max}) 120 / 250 W
Operate Time	Between Coil De-energization and NO Contact Opening 5 ... 15 ms Between Coil Energization and NO Contact Closing 30 ... 30 ms
Connecting Capacity Main Circuit	Flexible with Cable End 6 ... 16 mm ² Rigid Cable 6 ... 25 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Cable End 0.75 ... 2.5 mm ² Rigid Cable 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Connecting Terminals (delivered in open position) Main Poles	M 6 (+,-) pozidriv 2 screws with 1x (13 x 10 mm) connector
Terminal Type	Screw Terminals

Dimensions

Product Net Width	104 mm
Product Net Depth / Length	119.5 mm
Product Net Height	110 mm
Product Net Weight	1.43 kg

Popular Downloads

Data Sheet, Technical Information	1SNC001003C0202
Instructions and Manuals	FPTC407701P0003

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

